

24-Port Full Gigabit Managed Industrial Ethernet Switch

(B1-IPS33248FM-4GF)



OVERVIEW

The B1-IPS33248FM-4GF is a full gigabit L2+ managed industrial Ethernet fiber switch independently developed by BISMON. It has 20*10/100/1000Base-T RJ45 ports and 4*100/1000Base-X SFP fiber slot ports. Each port can support wire-speed forwarding.

The B1-IPS33248FM-4GF has L2+ full network management function, supports IPV4/IPV6 management, static route full line rate forwarding, complete security protection mechanism, ACL/QoS policy and rich VLAN functions, and is easy to manage and maintain. Supports multiple network redundancy protocols STP/RSTP/MSTP (<50ms) and (ITU-T G.8032) ERPS (<20ms) to improve link backup and network reliability. When one-way network fails, communication can be quickly restored to ensure important Uninterrupted communication for applications. According to the actual application requirements, you can configure multiple application services such as PoE power

management, port traffic control, VLAN division, and SNMP through the Web network management mode.

FEATURE

■ Gigabit access , SFP port uplink

- ◇ All series supports Ethernet port and SFP port combination, which enables users to flexibly build networking to meet the needs of various scenarios.
- ◇ Support non-blocking wire-speed forwarding.
- ◇ Support full-duplex based on IEEE802.3x and half-duplex based on backpressure.

■ Strong business processing capability

- ◇ IEEE802.1Q VLAN, flexible VLAN division, Voice VLAN and QinQ configuration.
- ◇ QoS, Priority mode based on 802.1P, Port & DSCP, queue scheduling algorithm including Equ, SP, WRR & SP+WRR.
- ◇ ALC, filter data packet through configuring matching rules, processing operation & time permission, and provide flexible and safe access control.
- ◇ IGMP V1/V2 and IGMP Snooping.
- ◇ ERPS/STP/RSTP/MSTP.
- ◇ Static and dynamic aggregation.

■ Security

- ◇ 802.1X authentication.
- ◇ Port isolation, Storm control.
- ◇ IP-MAC-VLAN-Port binding.

■ Stable and reliable

- ◇ CCC, CE, FCC, RoHS.

- ◇ Low power consumption, no fan , aluminum casing.
- ◇ The user-friendly panel, it can show the device status through the LED indicator of PWR, SYS,Link,L/A .

■ Easy operation and maintenance management

- ◇ HTTPS, SSLV3, and SSHV1/V2.
- ◇ RMON, system log, LLDP, and port traffic statistics.
- ◇ CPU monitoring, memory monitoring, Ping test, and cable diagnose.
- ◇ Web management, CLI command line (Console, Telnet), SNMP (V1/V2/V3).

TECHNICAL SPECIFICATION

| Model | B1-IPS33248FM | B1-IPS33248FM-4GF |
|----------------------------------|---|--|
| Interface Characteristics | | |
| Fixed Port | 12*10/100/1000Base-T uplink RJ45 ports (Data) 12*100/1000Base-X uplink SFP slot ports (Data) 1 * RS232 console port(115200,N,8,1) 2 set of V+, V- redundant DC power interface (6 Pin Phoenix terminal) Alarm switch (FAULT) | 20*10/100/1000Base-T uplink RJ45 ports (Data) 4*100/1000Base-X uplink SFP slot ports (Data) 1 * RS232 console port(115200,N,8,1) 2 set of V+, V- redundant DC power interface (6 Pin Phoenix terminal) Alarm switch (FAULT) |
| Ethernet Port | Port 1-12 support 10/100/1000Base-T ,auto-sensing ,Full/half duplex MDI/MDI-X self-adaption | Port 1-20 support 10/100/1000Base-T ,auto-sensing, Full/half duplex MDI/MDI-X self-adaption |

| | |
|----------------------------|---|
| Twisted Pair Transmission | 10BASE-T: Cat3,4,5 UTP(≤100 meter) 100BASE-TX: Cat5 or later UTP(≤100 meter) 1000BASE-T: Cat5e or later UTP(≤100 meter) |
| Optical Fiber Port | Gigabit SFP optical fiber interface, default matching optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC) |
| SFP Port Expansion | Turbo overclocking 2.5G optical module and ring |
| Optical Cable/ Distance | Multi mode: 850nm / 0 ~ 500M, single mode: 1310nm / 0 ~ 40KM, 1550nm 0 ~ 120KM. |
| Chip Parameter | |
| Network Management Type | L2+ |
| Network Protocol | IEEE802.3 10BASE-T, IEEE802.3i 10Base-T IEEE802.3u 100Base-TX , IEEE802.3ab 1000Base-T IEEE802.3z 1000Base-X IEEE802.3x |
| Forwarding Mode | Store and Forward(Full Wire Speed) |
| Switching Capacity | 256Gbps |
| Forwarding Rate@64byte | 35.71Mpps |
| MAC | 8K |
| Buffer Memory | 8M |
| Jumbo Frame | 9.6K |
| LED Indicator | Power: PWR (green), System: SYS (green), Network: Link (yellow), Fiber Port : L/A (green) |
| Reset Switch | Yes, One-button factory reset |
| Power | |
| Total PWR / Input | 36W /48VDC |


| | |
|---|--|
| Voltage | |
| Power Consumption | Standby<20W, Full load<30W |
| Working Voltage | 12-48VDC, 6 Pin industrial Phoenix terminal, support anti-reverse protection. |
| Power Supply | No, optional 24V/36W or 24V/60W industrial power supply |
| Physical Parameter | |
| Operation TEMP / Humidity | -40~+80°C;5%~90% RH Non condensing |
| Storage TEMP / Humidity | -40~+85°C;5%~95% RH Non condensing |
| Dimension (L*W*H) | 166*149*89mm |
| Net /Gross Weight | <2.2kg / <2.8kg |
| Installation | Desktop, DIN rail |
| Certification & Warranty | |
| Lightning protection / protection level | <p>Lightning protection: 6KV 8/20us; Protection level: IP40</p> <p>IEC61000-4-2(ESD):±8kV contact discharge,±15kV air discharge</p> <p>IEC61000-4-3(RS):10V/m(80~1000MHz)</p> <p>IEC61000-4-4(EFT): power cable:±4kV; data cable:±2kV</p> <p>IEC61000-4-5(Surge):power cable:CM±4kV/DM±2kV; data cable:±4kV</p> <p>IEC61000-4-6(radio frequency transmission):10V(150kHz~80MHz)</p> <p>IEC61000-4-8(power frequency magnetic field):100A/m;1000A/m ,1s to 3s</p> <p>IEC61000-4-9(pulsed magnet field):1000A/m</p> <p>IEC61000-4-10(damped oscillation):30A/m 1MHz</p> <p>IEC61000-4-12/18(shockwave):CM 2.5kV,DM 1kV</p> <p>IEC61000-4-16(common-mode transmission):30V; 300V,1s</p> <p>FCC Part 15/CISPR22(EN55022):Class A</p> <p>IEC61000-6-2(Common Industrial Standard)</p> |
| Mechanical | IEC60068-2-6 (anti vibration) |

| | |
|------------------------------------|--|
| Properties | IEC60068-2-27 (anti shock) IEC60068-2-32 (free fall) |
| Certification | CCC;CE mark, commercial; CE/LVD EN60950;FCC Part 15 Class B; RoHS; |
| Warranty | 5 years, lifelong maintenance. |
| Network Management Features | |
| Interface | IEEE802.3X (Full-duplex) Port temperature protection setting Port green Ethernet Energy-saving setting Broadcast storm control based on port speed The speed limit of the message flow in the access port. The minimum particle size is 64Kbps. |
| Layer 3 Features | L2+ network management ,IPV4/IPV6 management L3 soft routing forwarding, Static route, Default route @ 128 pcs, APR @ 1024 pcs |
| VLAN | 4K VLAN based on port, IEEE802.1q VLAN based on the protocol VLAN based on MAC Voice VLAN, QinQ configuration Port configuration of Access, Trunk, Hybrid |
| Port Aggregation | LACP, Static aggregation Max 12 aggregation groups and 8 ports per group. |
| Spanning Tree | STP (IEEE802.1d),RSTP (IEEE802.1w),MSTP (IEEE802.1s) |
| Industrial Ring | G.8032 (ERPS),Recovery time less than 20ms |
| Network Protocol | 250 Ring at most, Max 1024 devices per ring. |
| Multicast | MLD Snooping v1/v2,Multicast VLAN IGMP Snooping v1/v2, Max 1024 multicast groups, Fast log out |
| Port Mirroring | Bidirectional data mirroring based on port |
| QoS | Flow-based Rate Limiting |


| | |
|------------|--|
| | <p>Flow-based Packet Filtering</p> <p>8*Output queues of each port</p> <p>802.1p/DSCP priority mapping</p> <p>Diff-Serv QoS,Priority Mark/Remark</p> <p>Queue Scheduling Algorithm (SP, WRR, SP+WRR)</p> |
| ACL | <p>Port-based Issuing ACL,ACL based on port and VLAN</p> <p>L2 to L4 packet filtering, matching first 80 bytes message. Provide ACL based on MAC, Destination MAC address, IP Source, Destination IP, IP Protocol Type, TCP/UDP Port, TCP/UDP Port Range, and VLAN, etc.</p> |
| Security | <p>IP-MAC-VLAN-Port binding</p> <p>ARP inspection,Anti-DoS attack</p> <p>AAA & RADIUS,MAC learning limit</p> <p>Mac black holes,IP source protection</p> <p>IEEE802.1X & MAC address authentication</p> <p>Broadcast storm control,Backup for host datum</p> <p>SSH 2.0,SSL,Port isolation,ARP message speed limit</p> <p>User hierarchical management and password protection</p> |
| DHCP | <p>DHCP Client,DHCP Snooping, DHCP Server,DHCP Relay</p> |
| Management | <p>One-key recovery</p> <p>Cable Diagnose,LLDP</p> <p>Web Management (HTTPS)</p> <p>NTP,System work log,Ping Test</p> <p>CPU instant utilization status view</p> <p>Console/AUX Modem/Telnet/SSH2.0 CLI</p> <p>Download & Management on FTP, TFTP, Xmodem, SFTP,SNMP</p> <p>V1/V2C/V3</p> <p>NMS - smart network management system platform(LLDP+SNMP)</p> |
| System | <p>Category 5 Ethernet network cable</p> <p>Web browser: Mozilla Firefox 2.5 or higher, Google browser chrome V42</p> |

or higher, Microsoft Internet Explorer10 or later;
TCP/IP, network adapter, and network operating system (such as
Microsoft Windows, Linux, or Mac OS X) installed on each computer in a
network

DIMENSION



APPLICATION



ORDERING INFORMATION

| Model | Description | Recommended Power Supply |
|-------------------|---|--------------------------|
| B1-IPS33248FM-4GF | L2+ managed industrial Ethernet fiber switch with 20*10/100/1000M RJ45 ports and 4*100/1000M SFP slot ports. Support dual DC power supply input and DIN rail mounting. | 36W/60W |
| B1-IPS33248FM | L2+ managed industrial Ethernet fiber switch with 12*10/100/1000M RJ45 ports and 12*100/1000M SFP slot ports. Support dual DC power supply input and DIN rail mounting. | 36W/60W |

Note: Industrial Ethernet switch does not match the SFP optical module and power supply.

PACKING LIST

| PACKING LIST | CONTENT | QTY | UNIT |
|--------------|---|-----|------|
| | 24-port full gigabit managed industrial Ethernet switch | 1 | SET |
| | RJ45-DB9 Line | 1 | PC |
| | User Guide | 1 | PC |
| | Warranty Card | 1 | PC |

OPTICAL MODULE INFORMATION

| Product | Model | Description | Unit |
|----------------------------|-----------|---|------|
| 1.25G Optical Module | B1-2630 | SFP optical module, 1.25G, multi mode dual fiber 850nm, transmission distance: 550m, LC interface, support DDM function, support hot plug and pull. | PC |
| | B1-2632 | SFP optical module, 1.25G, single-mode dual fiber 1310nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull. | PC |
| | B1-2612-T | SFP optical module, 1.25G, single-mode single fiber TX1310nm/RX1550nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull. | PC |
| | B1-2613-R | SFP optical module, 1.25G, single-mode single fiber TX1550nm/RX1310nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull. | PC |
| | 2612-T-G | Industrial SFP optical module, 1.25G, single-mode single fiber TX1310nm/RX1550nm, transmission | PC |

| | | | |
|--------------|---------------|---|----|
| | | distance: 20km, LC interface, support DDM function, support hot plug and pull. | |
| | 2613-R-G | Industrial SFP optical module, 1.25G, single-mode single fiber TX1550nm/RX1310nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull. | PC |
| | B1-2612-T-S C | SFP optical module, 1.25G, single-mode single fiber TX1310nm/RX1550nm, transmission distance: 20km, SC interface, support DDM function, support hot plug and pull. | PC |
| | B1-2613-R-S C | SFP optical module, 1.25G, single-mode single fiber TX1550nm/RX1310nm, transmission distance: 20km, SC interface, support DDM function, support hot plug and pull. | PC |
| Power Module | B1-2633 | 1.25G SFP optical module transfers to 10/100/1000M RJ45 port. | PC |

POWER SUPPLY SELECTION TABLE

| Product | Model | Description | Unit |
|--------------------------------------|-------------|--|------|
| 36W DIN Rail Industrial Power Supply | GWS-DP36-24 | Din Rail type 36W single set of output power supply; Input Voltage:AC 100V~240V 50-60Hz, 0.56A Output Voltage:DC 24V 1.5A Operation Temperature:-40℃—+70℃ | PC |

| | | | |
|--|-------------|---|----|
| 60W DIN Rail Industrial Power Supply | GWS-DP60-24 | Din Rail type 60W single set of output power supply; Input Voltage:AC 100V~240V 50-60Hz, 1.0A Output Voltage:DC 24V 2.5A Operation Temperature:-40℃—+70℃ | PC |
|--|-------------|---|----|

RELATED PRODUCT

| Model | Description |
|-----------------------|--|
| B1-IPS33064FM | L2+ managed industrial Ethernet fiber switch with 4*10/100/1000M RJ45 ports and 2*100/1000M SFP slot ports. Support dual DC power supply input and DIN rail mounting. |
| B1-IPS33084FM | L2+ managed industrial Ethernet fiber switch with 4*10/100/1000M RJ45 ports and 4*100/1000M SFP slot ports. Support dual DC power supply input and DIN rail mounting. |
| B1-IPS33108FM | L2+ managed industrial Ethernet fiber switch with 8*10/100/1000M RJ45 ports and 2*100/1000M SFP slot ports. Support dual DC power supply input and DIN rail mounting. |
| B1-IPS33148FM | L2+ managed industrial Ethernet fiber switch with 10*10/100/1000M RJ45 ports and 4*100/1000M SFP slot ports. Support dual DC power supply input and DIN rail mounting. |
| B1-IPS33168FM | L2+ managed industrial Ethernet fiber switch with 8*10/100/1000M RJ45 ports and 8*100/1000M SFP slot ports. Support dual DC power supply input and DIN rail mounting. |
| B1-IPS33168FM-4 GF | L2+ managed industrial Ethernet fiber switch with 12*10/100/1000M RJ45 ports and 4*100/1000M SFP slot ports. Support dual DC power supply input and DIN rail mounting. |

