





CCT - Connector Cleaning Tips

Noyes Fiber Systems is pleased to announce a new fiber connector end-face cleaning technology. Rather than a fabric-covered or foam-covered stick, we are offering a molded cleaning tip that will trap contamination and wick cleaning solvents from bulkhead connectors. This new cleaning tip is a molded, sintered polymer that is both porous and pliable conforming to virtually any fiber end-face polish geometry while trapping and absorbing contaminants.

the product

- Molded sintered polymer construction assures perfect bulkhead fit and consistent performance with each cleaning tip
- No fibers, binders, adhesives or outgassing that may contaminate the connector
- Traps and holds liquid and particle contaminants in an absorbent open cell matrix ranging from 10-25 microns
- The elastic cleaning head enhances entrapment of particles and oils, while allowing the tip to conform to virtually any fiber end-face geometry (8 degree, domed polish, etc.)
- Very absorbent
- US and Foreign patents pending

the wet/dry cleaner

- Dual-head design permits wet and dry cleaning in one swab
- Solvent and chemical resistant, not physically altered by solvent contact
- Designed to work with Noyes FCC2,
 Fiber Connector Cleaner
- Most connectors cleaned the first time

configured for the job

- Cleaning tip exposed for cleaning ferrule end-faces in alignment sleeves that are recessed within sockets or bulkhead adaptors
- Also available with cleaning tips recessed in the "straw" for cleaning exposed ferrules and termini (jumpers)
- Cleaning tips available for most common commercial and Mil Spec ferrule sizes

Size (diameter of ferrule or termini)	Type (Pin - for exposed ferrules and termini Socket - for ferrules and termini in alignment sleeves)	Part Number	Comments
2.5mm	Pin	CCTP-25-0900	Examples: SC, ST, FC, etc.
2.5mm	Socket	CCTS-25-0900	Examples: SC, ST, FC, etc.
2.0mm	Pin	CCTP-25-0900	Mil T 29504/14 For Mil C 28876
2.0mm	Socket	CCTS-16-0900	Mil T 29504/15 For Mil C 28876
1.6mm	Pin	CCTP-25-0900	Mil T 29504/04 For Mil C 38999
1.6mm	Socket	CCTS-16-0900	Mil T 29504/05 For Mil C 38999
1.25mm	Pin	CCTP-25-0900	Examples: LC, MU
1.25mm	Socket	CCTS-12-0900	Examples: LC, MU
MT ferrule	Pin	CCTX-MT-0900	Examples: MTP®*, MPX®**
MT ferrule	Socket	CCTX-MT-0900	Examples: MTP®*, MPX®**

^{*} Registered Trademark of US Conec Ltd.

^{**} Registered Trademark of TYCO Electronics Corp.

