


Adopted by Multinationals Worldwide as Their chosen cleaning Method

CLETOP[®] SERIES


Reel Type



CLETOP (replacement reel)



Stick Type



Type $\phi 2.5\text{mm}$



Type $\phi 1.25\text{mm}$



Cleaning of connectors used in high definition television camera



Type $\phi 2.0\text{mm}/2.5\text{mm}$ Double Ended

NTT-ME always offers the most reliable and effective connector cleaning tools. Reliability makes the world choose CLETOP series.

NTT-ME's CLETOP series easily and quickly cleans ferrule end-faces, the most important component in maintaining the quality of fiber-optic connections. It's an alcohol-free dry cloth solution.

●Reel type/for ferrule end-faces of connector plug

CLETOP-S (replacement cartridge)



Easy to replace tape cartridge

The tape can be replaced very easily by a "drop-in" cartridge.



One push operation

Available for both left handed and right handed operators.



Anti-static material

Adopt anti-static material for body and replacement cartridge.

TypeA TypeB

note) Applicable connectors for Type A and Type B are shown on back side

●Reel type/for ferrule end-faces of connector plug


CLETOP (replacement reel)



TypeA TypeB

●for multi-fiber pinned connectors

Type MPO with pins Type MT-RJ with pins




Features


- Easy to use and efficient. Delivers consistently high quality cleaning performance.
- Palm-sized and lightweight. Easy and safe to use whether in the engineering lab., on the production line, or in the field.
- Cleaning tape is replaceable and cost-effective.
- One cleaning reel / cartridge provides more than 400 ferrule cleaning cycles.

●For multi-fiber pinned connectors (MPO& MT-RJ)


NTT-ME has designed the rubber pad to enable effective cleaning of an MPO/MT-RJ ferrule end-face, between the pins, without damaging the pins (PAT.P).




End-faces of the pinned connector before/after use of the CLETOP



Ferrule end-faces before/after use of the CLETOP series




Ultra-fine Micro-fibers deliver outstanding cleaning performance in removing contamination.



●Stick type/for ferrule end-faces and inside sleeves

CLETOP (replacement stick)

Type2.5mm Type1.25mm



Designed for connectors used in high definition camera's

Type2.0mm Type 2.0/2.5mm double ended




Features

- Easy to clean ferrule end-faces inside the adapters.
- Lightweight and safe to use.
- Compact and disposable.

How to clean?

Ex. SC connector(φ2.5mm)





- ① Ensure that stick is held straight when inserting into sleeve.
- ② Load: Apply sufficient pressure (approx 600~700g) to ensure ferrule a little depressed in sleeve.
- ③ Rotate stick clockwise 4~5 times, while ensuring direct contact with ferrule end-face is maintained.

Notice: cleans per stick; Maintenance (repair) 1 cleaning/piece





Specification

CLETOP-S Reel type <replacement cartridge>

Specification	Reel type	
Type	Type A	Type B
Part No.	14110501	14110601
Shape of rubber pad		
Cleans per cartridge	more than 400 times	more than 400 times
Connectors cleaned	SC,SC2,FC,ST DIN,D4	MU,LC,MT MPO,MT-RJ without pins Biconic
Dimension WxHxD (mm)	125 × 85 × 35	
Weight (g)	150	150
Packaging	1	1
Remarks	—	—

Consumables	Replacement cartridge blue (6 pcs/set)	Replacement cartridge white (6 pcs/set)
Part No. of consumable	14110700	14110710

CLETOP® Reel type <replacement reel>

Specification	Reel type			
Type	Type A	Type B	Type MT-RJ	Type MPO
Part No.	14100501	14100601	14100101	14100201
Shape of rubber pad				
Cleans per reel	more than 400 times	more than 400 times	more than 400 times	more than 400 times
Connectors cleaned	SC,SC2,FC,ST DIN,D4	MU,LC,MT MPO,MT-RJ without pins Biconic	MT-RJ with pins	MPO with pins
Dimension WxHxD (mm)	130 × 75 × 40			
Weight (g)	160	160	160	160
Packaging	1	1	1	1
Remarks	—	—	—	—

Consumables	Replacement reel blue (6 pcs/set)	Replacement reel white (6 pcs/set)
Part No. of consumable	14100700	14100710

CLETOP® Stick type

Specification	Stick type			
Type	Type 2.5mm	Type 1.25mm	Type 2.0mm	Type 2.0/2.5mm
Part No.	14100400	14100401	14100402	14100403
Cleans per stick	Maintenance (for repair) 1 cleaning/piece			
Connectors cleaned	SC,SC2,FC,ST,DS	MU,LC	for connectors for high definition television camera	
Dimension L (mm)	146	101	146	127
Packaging	200 pcs/set	200 pcs/set	200 pcs/set	100 pcs/set
Remarks	—			double ended

Notice 1: Please do not use this product for other purposes than cleaning the ferrule end-faces.

Notice 2: The cleaning performance may change depending upon the environment and the contamination types.

NTT-ME



NTT-ME CORPORATION
Carrier Business Department
Global Solution Headquarters
(Junkan Business Headquarters IX)

AXIS Ikebukuro Bldg.,
23-5, Higashi-Ikebukuro 3-chome,
Toshima-ku, Tokyo 170-0013 Japan
TEL 81-3-5956-9025 FAX 81-3-5956-9039
E-Mail :opt-g@ntt-me.co.jp
URL: <http://nttlivs.ntt-me.co.jp/opt-e/>

Optimark

14 Heath Wood Lane

Chestnut Hill, MA 02467-2685, USA

Tel: (617) 232-6224 Fax: (617) 731-2272

www.optimark-fiber.com sales@optimark-fiber.com

