

# Product datasheet

Specifications



APC Smart-UPS C, Line Interactive, 3kVA, Tower, 230V, 8x IEC C13+1x IEC C19 outlets, USB and Serial communication, AVR, Graphic LCD

SMC3000I

## Overview

**Presentation** Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

**Lead time** Usually Ships within 2 Weeks

## Main

**Main Input Voltage** 230 V

**Other Input Voltage** 220 V  
240 V

**Main Output Voltage** 230 V

**Rated power in W** 2100 W

**Rated power in VA** 3000 VA

**Input Connection Type** IEC 320 C20

**Output connection type** 8 IEC 320 C13  
1 IEC 320 C19

**Number of rack unit** 0U

**Battery type** Lead-acid battery

**Provided equipment** CD with software  
Documentation CD  
USB cable

## General

**Number of power module filled slots** 0

**Number of power module free slots** 0

**Product web sub-family** Entry level

**Redundant** No

## Physical

**Colour** Black

**Height** 43.5 cm

**Width** 19.7 cm

**Depth** 54.4 cm

**Product weight** 43 kg

Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

## Input

Input voltage limits	170...300 V adjustable 180...287 V
Network frequency	47...63 Hz

## Output

Harmonic distortion	Less than 5 % at full load
Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2100 W
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50 Hz sync to mains

## Conformance


Product certifications	C-Tick CE EAC GOST SABS VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

Acoustic level	45 dBA
Heat dissipation	135 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

## Batteries & Runtime

Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1

Battery life	3...5 year(s)
Replacement battery	<a href="#">APCRBC150</a> 
Battery power in VAH	552 VAh runtime
Battery charger power	183 W rated

## Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Control panel	Multifunction LCD status and control console
Free slots	0

## Surge Protection and Filtering

Surge energy rate	300 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	76.2 cm
Package 1 Width	69.9 cm
Package 1 Length	38.1 cm
Package 1 Weight	51 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Recommended replacement(s)