

Technical Specifications

APC Smart-UPS, Line Interactive, 3kVA, Tower, 230V, 8x IEC C13+2x IEC C19 outlets, SmartConnect Port+SmartSlot, AVR, LCD | SMT3000IC |
Downloaded on 12/17/2022 (EST)



APC Smart-UPS, Line Interactive, 3kVA, Tower, 230V, 8x IEC C13+2x IEC C19 outlets, SmartConnect Port+SmartSlot, AVR, LCD

SMT3000IC

Call for More Information

- Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
- Includes: USB cable

Output	
Output power capacity	2.7kWatts / 3.0kVA
Max Configurable Power (Watts)	2.7kWatts / 3.0kVA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Output Voltage Distortion	Less than 5 %
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz Sync to mains
Other Output Voltages	220 V, 240 V
Topology	Line interactive
Waveform type	Sine wave
Output Connections	(8) IEC 320 C13 (1) IEC 320 C19 (2) IEC Jumpers
Transfer Time	6 ms typical : 10 ms maximum

Input	
Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz Auto-sensing
Input Connections	BS1363A British, IEC 320 C20, Schuko CEE 7 / EU1-16P
Input voltage range for main operations	151 - 302 Adjustable, 160 - 286V
Number of Power Cords	1
Other Input Voltages	220 V, 240 V

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Smart-UPS, Line Interactive, 3kVA, Tower, 230V, 8x IEC C13+2x IEC C19 outlets, SmartConnect Port+SmartSlot, AVR, LCD | SMT3000IC |
Downloaded on 12/17/2022 (EST)



Batteries & Runtime	
Battery type	Lead-acid battery
Typical recharge time	3hour(s)
Replacement Battery	RBC55
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Charge Power (Watts)	271 Watts
Extendable Run Time	1
Runtime	View Runtime Graph (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	SmartSlot, USB
Control panel	Multifunction LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	Yes
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering	
Surge energy rating	365Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical	
Maximum Height	435MM, 43.5CM
Maximum Width	197MM, 19.7CM
Maximum Depth	544MM, 54.4CM
Net Weight	52.5KG
Shipping weight	63.7KG
Shipping Height	699MM, 69.9CM
Shipping Width	762MM, 76.2CM
Shipping Depth	381MM, 38.1CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Smart-UPS, Line Interactive, 3kVA, Tower, 230V, 8x IEC C13+2x IEC C19 outlets, SmartConnect Port+SmartSlot, AVR, LCD | SMT3000IC |
Downloaded on 12/17/2022 (EST)

Physical	
Color	Black

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 15240meters
Audible noise at 1 meter from surface of unit	53.0dBA
Online thermal dissipation	375.0BTU/hr

Conformance	
Approvals	CE, EAC, RCM, VDE
Standard warranty	3 years repair or replace (excluding battery) and 2 years for battery, optional on-site warranties available, optional extended warranties available

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.